

520是缝编毡的专用合股无捻粗纱，适用于不饱和聚酯树脂、乙烯基树脂、环氧树脂等。

该产品广泛用于各类缝编毡，主要用于生产玻璃钢船体、汽车外壳、型材等。

520 Assembly Roving is specially designed for stitch mats application. It is compatible with unsaturated polyester, vinyl ester and epoxy resins.

520 is widely used in various weaving processes to manufacture boat hulls, automotive parts and profiles.

产品特点

- ◎ 树脂浸透性好
- ◎ 分散性好
- ◎ 切割性好
- ◎ 抗静电性好

Product Features

- ◎ Moderate wet-out in resin.
- ◎ Good choppability.
- ◎ Good dispersion.
- ◎ Good anti-static property.

规格代号 Identification:

代号示例 Example	ER13-2400-520
玻璃类型 Glass Type	E
合股无捻粗纱 Assembled Roving	R
纤维直径 Filament Diameter (μm)	13
线密度 Linear Density (tex)	2400
浸润剂代号 Size Code	520




技术指标 Technical Parameters

线密度偏差 Linear Density (%)	含水率 Moisture Content (%)	可燃物含量 Size Content (%)	硬挺度 Stiffness (mm)
ISO 1889	ISO 3344	ISO 1887	ISO 3375
± 4	≤ 0.10	0.90 ± 0.15	135±15 120±15 (33)

贮存 Storage

在没有特殊要求的情况下，玻璃纤维产品应贮存在干燥、凉爽的地方，防止受潮。建议保持室内温度平衡，最佳存储条件为温度-10°C~35°C，相对湿度≤80%。本产品12个月内使用最佳，使用前应保持在原包装内，为确保安全，避免损坏产品，托盘的堆码高度不应超过三层。当堆放两层或三层高时，要求正确地、平稳地移动上面的托盘。

Unless otherwise specified, the fiberglass products should be stored in a dry, cool and moisture-proof area. The fiberglass products should remain in their original package until prior to use. The room temperature and humidity should be always maintained at -10°C~35°C and ≤80% respectively. To ensure safety and avoid damage to the product, the pallets should not be stacked more than three layers high. When the pallets are stacked in 2 or 3 layers, special care should be taken to correctly and smoothly move the top pallet.



包装信息 Packaging

* 采用托盘包装或小纸箱包装

The product can be packed on pallet or in small cardboard boxes.

纱团高度 Package height mm (in)	260 (10.2)	260 (10.2)
纱团内径 Package inside diameter mm (in)	100 (3.9)	100 (3.9)
纱团外径 Package outside diameter mm (in)	270 (10.6)	310 (12.2)
纱团重量 Package weight kg (lb)	17 (37.5)	23 (50.7)

层数 Number of layers	3	4	3	4
每层纱团个数 Number of doffs per layer	16		12	
每托纱团个数 Number of doffs per pallet	48	64	36	48
每托重量 Net weight per pallet kg (lb)	816 (1799)	1088 (2398.6)	828 (1825.4)	1104 (2433.9)

托盘长度 Pallet length mm (in)	1120 (44.1)	1270 (50)
托盘宽度 Pallet width mm (in)	1120 (44.1)	960 (37.8)
托盘高度 Pallet height mm (in)	940 (37)	1200 (47.5)

中国巨石股份有限公司 CHINA JUSHI CO., LTD.

版权所有 © 巨石集团有限公司 巨石集团有限公司注册商标

地址: 浙江省桐乡经济开发区, 邮编: 314500 Add: Tongxiang Economic Development Zone, Zhejiang 314500, China

(国内销售 Domestic Sales) 电话Tel:+86-573-88181016 传真Fax:+86-573-88136248
(国际销售 International Sales) 电话Tel:+86-573-88136318 传真Fax:+86-573-88181058
(客户服务 Customer Service) 电话Tel:+86-573-88136325 传真Fax:+86-573-88136248

http://www.jushi.com E-mail: info@jushi.com